

HUBER+SUHNER® DATA SHEET

RF TERMINATION: Type 65_BNC-75-0-7/133_N

Rev.: F



Description

Standard Termination, Low Power

Product Configuration

Connector BNC plug (male)

Technical Data

Electrical Data

Nominal impedance 75 Ω
Frequency range DC to 1 GHz
VSWR $\leq 1.01 + 0.21 f$
Power rating 1 Watt average power to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature.
2000 Watt peak power

Mechanical Data

Dimensions 14.5 / 14.5 / 24.9 (height / width / length coaxial in mm)
Weight 0.0101 kg

Material Data

Piece Part

Centre contact
Outer contact
Body
Insulator
Coupling nut

Material

Brass
Brass
Brass
PFA / PTFE
Brass

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating



Related Documents

Outline drawing On request

Ordering Information

Single packaging 65_BNC-75-0-7/133_NE

Additional Information

Remarks

Interface dimensions acc. to IEC 60169-8_MIL-STD-348A/301_CECC 22120

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions